



KONUS KONEX d.o.o. - PE KOFIL,
Mestni trg 18, 3210 SLOVENSKE KONJICE, SLOVENIA

Tel.: ++ 386 03 5753 812, 7573 100; Fax: ++ 386 03 5754 368, 5754 140; E-mail: info@konus-konex.si

QUALITY STANDARD **KOFIL**



PRODUCT: KOFIL FF 20/600 G

CHARACTERISTIC:	VALUE:	MEASURE UNIT:	CONTROL METHOD:
Chemical composition	100 % Polyester (heat set)		
Weight	600	g/m ²	A 23388
Thickness	20	mm	A 23388
Filter class	EU5 F5		DIN 24185 EN 779
Temperature resistance	70 - 90	°C	
Holding of synthetic dust parts (A)	97	%	DIN 24185
Efficiency on atmospheric dust (E)	46	%	DIN 24185
Holding of parts between 10-15 microns	> 99	%	
Holding of parts above 15 microns	100	%	
Air velocity	0,25	m/s	
Initial pressure drop	23	Pa	
Final pressure drop (recommendable)	300	Pa	
Dust holding capacity	390	g/m ²	
Flame retardant	F1 (selfextinguished)		DIN 53438

Signature:

Date: 16.06.2005