

Quality standard



PRODUCT: **KOFIL F10/150**

DATE: **5.10.2011**

PRODUCER: **Konus Konex, d.o.o.**

PRODUCT NUMBER: **0439789**

CHEMICAL COMPOSITION: **100% POLYESTER (HEAT SET)**

PRODUCT CHARACTERISTICS:

Nr.	CHARACTERISTIC	MEASURE UNIT	VALUE	CONTROL METHOD
1	Weight	g/m ²	150	A 23388
2	Thickness	mm	10	A 23388
3	Colour		white	
4	Filter class		EU2 (G2)	DIN 24185 (EN 779)
5	Temperature resistance	°C	70 - 90	
6	Holding of synthetic dust parts (A)	%	79	DIN 24185
7	Efficiency on atmospheric dust (E)	%	-	DIN 24185
8	Air velocity	m/s	1,5	
9	Initial pressure drop	Pa	25	
10	Final pressure drop (recommendable)	Pa	200	
11	Dust holding capacity	g/m ²	380	
13	Flame retardant		F1 (self-extinguishing)	DIN 53438

Please note: values given may be subject to change without notice.

Consult Konus Konex before using these values for design or specification.

Please note this data sheet will supersede any previous version.

SIGNATURE OF KONUS KONEX:

Konus Konex Ltd, 3210 Slovenske Konjice, Mestni trg 18, Slovenija, EU

T: +386 3/ 757 3 100, F: +386 3/ 575 4 140, 575 4 368

E: info@konuskonex.com, www.konuskonex.com, www.kofil.com